Datenblatt KKW Kassengerät 5.3 kW
KKW Professional R32 EU standart A+++
Specification:

Model			**18000BTU**
Power supply (Outdoor)		V- Ph-Hz	220-240v/50HZ
Cooling (Standard conditions)	Capacity	Btu/h	18000 （9900~19064)
	Input	W	1220 (~2510)
Heating (Standard conditions)	Capacity	Btu/h	19000 （8100~20800)
	Input	W	1300 (~2950)
Seasonal Cooling	Pdesignc	kW	5.3
	SEER	W/W	7.61
	Energy Efficiency Class		A++
Heating(Average)	Pdesignh	kW	5.6
	SCOP	W/W	4.31
	Energy Efficiency Class		A++
Tol		℃	-15
Indoor fan motor	Model		ZKFP-46-8-1
	Qty		1
	Input	W	45
	Speed(Hi/Mi/Lo)	r/min	752/664/576
Indoor coil	a.Number of rows		2
	b.Tube pitch(a)x row pitch(b)	mm	21x13.37
	c.Fin spacing	mm	1.3
	d.Fin type (code)		Hydrophilic aluminum
	e.Tube outside dia.and type	mm	Φ7,Inner groove tube
	f.Coil length x height x width	mm	1360x210x26.74
	g.Number of circuits		4
Indoor air flow (Hi/Mi/Lo)		m3/h	680/584/479
Indoor noise level (Hi/Mi/Lo/Si)		dB(A)	45.4/44/39//
Indoor sound power level		dB(A)	59
Throttle type		/	
Indoor unit	Dimension(W*D*H)(body)	mm	570x570x260
	Dimension (W x Dx	mm	647x647x50
	Packing (W*D*H)(body)	mm	662x662x317
	Packing (W x Dx H)(panel)	mm	715x715x123
	Net/Gross weight(body)	kg	16/20.6
	Net/Gross weight(panel)	kg	2.5/4.5
Drainage water pipe dia		mm	ODΦ25mm
Qty'per 20' /40' /40'HQ		Indoor unit	186/375/429

Compressor	Model		KSN140D21UFZ
	Type		ROTARY
	Brand		GMCC
	Capacity	W	4385
	Input	W	1140
	Thermal protector		/
	Thermal protector position		/
	Capacitor	μF	/
	Refrigerant oil/oil charge	ml	VG74 440
Outdoor fan motor	Model		ZKFN-34-10-1
	Input	W	/
	Speed	r/min	760/650
Outdoor coil	a.Number of rows		2
	b.Tube pitch(a)x row pitch(b)	mm	21x22
	c.Fin spacing	mm	1.3
	d.Fin type (code)		Hydrophilic aluminum
	e.Tube outside dia.and type	mm	Φ7,Inner groove tube
	f.Coil length x height x width	mm	860*504*44
	g.Number of circuits		4
Outdoor air flow		m3/h	2100
Outdoor sound pressure level		dB(A)	46.0
Outdoor sound power level		dB(A)	63.0
Throttle type		/	(EXV)
Outdoor unit	Dimension(W*D*H)	mm	805x330x554
	Packing (W*D*H)	mm	915x370x615
	Net/Gross weight	kg	32.5/35.2
Refrigerant	Type		R32
	GWP		675
	Charged quantity	kg	1.15
Design pressure		MPa	4.3/1.7
Refrigerant piping	Liquid side/ Gas side	mm(inch)	6.35mm(1/4in)/12.7mm(1/2in)
	Max. refrigerant pipe length	m	30
	Max. difference in level	m	20
Thermostat type			(Remote Control)
Room temperature	Indoor(cooling/ heating)	℃	17～32/0～30
	Outdoor(cooling/heating)	℃	-15～50/-15～24
Application area (Cooling Standard)		m2	24～35
Qty'per 20' /40' /40'HQ		Outdoor unit	114/234/312