Datenblatt KKW Multisplit Aussengerät für 4 IE:
KKW Professional R32 EU standard A+++ Inverter Wall Split Mounted
Specification:

KKW Professionel Outdoor unit specifications			
Model Number			**FH23RI63-OMSWK (max. 4 Stk. IE)**
Control type			
Heat Exchangers			
Cooling capacity		Btu/h	36000
		W	10500
Heating capacity		Btu/h	38000
		W	10900
SEER (Class)		W/W	6.31 (A+++)
SCOP (Class)			4.6 (A++)
Outdoor sound power pressure			48
Outdoor sound power level		dB(A)	60
Power supply			220 - 240V~ / 50HZ
Voltage Range		V	165~265
Power input	Cooling	W	2765 (~3800)
	Heating		2547 (~4600)
Operating Current	Cooling	A	13 (~18.1)
	Heating		14.1 (~21.5)
Refrigerant / Charge		Gram	
CO2 equivalent		Tonnes	1.485
Compressor type			Twin Rotary
Compressor brand			SANYO
Outdoor fan type			axial-flow
Outdoor fan speed		rpm	850
Outdoor fan motor output		W	≤120
Number of rows			2
Number of U tube			42
Tube outside dia		mm	7
Tube type			Rifled tube
Fin spacing		mm	1.6
Fin type			Corrugated sheet
Tube pitch (a) * row pitch (b)		mm	18.2 * 21
Refrigerant coupling			Flare
High & low pressure valve	Liquid	Inches	1/4''
	Gas		3/8''
Net dimensions (W * H * D)		mm	990 * 910 * 340
Net weight		kg	68
Packing dimensions (W * H * D)		mm	1030 * 950 * 430
Gross weight		kg	80

Connecting Pipe	Liquid	Inches	1/4'' 4 x
	Gas		3/8'' 4 x
	Maxium length for each indoor unit		20m
	Maxium heigth difference		10m
	Standard weight charged		5m/indoor unit
	Extra weight charge		15g/m

Match Table	
Outdoor unit	FH23RI23-OMSWK
Standard indoor combination under Erp	9,000+9,000+9000+9000
One Indoor unit	N/A
Two Indoor units	9,000+9000, 9000+12000, 12000+12000, 9000+18000, 12000+18000, 18000+18000
Three Indoor units	9000+9000+9000, 9000+9000+12000, 9000+12000+12000, 9000+9000+18000, 9000+12000+18000, 12000+12000+12000, 12000+12000+18000
Four Indoor units	9000+9000+9000+9000, 9000+9000+9000+12000, 9000+9000+9000+18000, 9000+9000+12000+12000, 9000+12000+12000+12000