Datenblatt KKW Twin 2 x Kanalgerät 7 kW
KKW Professional R32 EU standart A+++
Specification:

Model			**2 x 24000BTU**
Power supply　(Outdoor)		V- Ph-Hz	3x400V/50HZ
Cooling (Standard conditions)	Capacity	Btu/h	2x24000（11263~27000)
	Input Outdoor unit	W	4060 (~6100)
Heating (Standard conditions)	Capacity	Btu/h	2x26000（9577~30500)
	Input Outdoor unit	W	4280 (~6900)
Seasonal Cooling	Pdesignc	kW	2x7.0
	SEER	W/W	9
	Energy Efficiency Class		A+++
Heating(Average)	Pdesignh	kW	2x8
	SCOP	W/W	4.52
	Energy Efficiency Class		A+++
Tol		℃	-15
Indoor fan motor	Model		ZKFN-45-8-1
	Qty		1
	Input	W	/
	Speed(Hi/Mi/Lo)	r/min	608/552/496
Indoor coil	a.Number of rows		2
	b.Tube pitch(a)x row pit	mm	21x13.37
	c.Fin spacing	mm	1.3
	d.Fin type (code)		Hydrophilic aluminum
	e.Tube outside dia.and t	mm	Φ7,Inner groove tube
	f.Coil length x height x w	mm	2135x168x26.74
	g.Number of circuits		4
Indoor air flow (Hi/Mi/Lo)		m3/h	1129/1035/826
Indoor noise level (Hi/Mi/Lo/Si)		dB(A)	50/47.5/42/29
Indoor sound power level		dB(A)	59
Throttle type		/	
Indoor unit	Dimension(W*D*H)(bod	mm	1100x774x249
Drainage water pipe dia		mm	ODΦ25mm

1 Aussengerät 14kW

Compressor	Model		KTQ420D1UMU
	Type		ROTARY
	Brand		GMCC
	Capacity	W	13700
	Input	W	3700
	Thermal protector		INT01L-4639
	Thermal protector position		EXTERNAL
	Capacitor	μF	/
	Refrigerant oil/oil charge	ml	VG74/1400
Outdoor fan motor	Model		ZKFN-85-8-22-5
	Input	W	126
	Speed	r/min	830/650
Outdoor coil	a.Number of rows		1.5
	b.Tube pitch(a)x row pit	mm	25.4x22
	c.Fin spacing	mm	1.4
	d.Fin type (code)		Hydrophilic aluminum
	e.Tube outside dia.and t	mm	Φ9.52,Inner groove tube
	f.Coil length x height x w	mm	990*610*44
	g.Number of circuits		4
Outdoor air flow		m3/h	7500
Outdoor sound pressure level		dB(A)	50.0
Outdoor sound power level		dB(A)	65.0
Throttle type		/	(EXV+Capillary)
Outdoor unit	Dimension(W*D*H)	mm	952x415x1333
	Packing (W*D*H)	mm	1095x495x1480
	Net/Gross weight	kg	103.7/118.3
Refrigerant	Type		R32
	GWP		675
	Charged quantity	kg	2.9
Design pressure		MPa	4.3/1.7
Refrigerant piping	Liquid side/ Gas side	mm(inch)	9.52mm(3/8in)/15.9mm(5/8in)
	Max. refrigerant pipe ler	m	75
	Max. difference in level	m	30
Thermostat type			(Remote Control)
Room temperature	Indoor(cooling/ heating)	℃	16～32/0～30
	Outdoor(cooling/heating	℃	-15～50/-15～24
Application area (Cooling Standard)		m2	64～94
Qty'per 20' /40' /40'HQ		Outdoor unit	22/48/48